



HUSQVARNA 321S15

Husqvarna 321S15 is a powerful sprayer with large mixture tank for efficient plant care work.

High quality materials

The high quality materials such as brass pump with plated pistons and stainless steel in spray lance secures a sufficient product lifetime and low service cost.



Smart Start®

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.

Comfortable harness

The harness is developed to be comfortable for the operator. The back padding is ventilated and the shoulder straps are broad to give maximum support.

Several nozzle options

Delivered with a straight 90cm adjustable nozzle and a 3 lance nozzle with extension. The connection has a swivel. All for effective use in various applications.

FEATURES

- Broad straps and ventilated back padding make the harness comfortable to wear.
- Smart Start® for easy starting
- Long lifetime is secured by choice of high quality materials.
- comes with a nozzle kit to be effectively used in various applications.
- The water tank is made of transparent material.
- The harness can easily be cleaned.

Technical specifications	
CAPACITY	
Clutch engagement speed (± 120)	4000 rpm
Idling speed	3000 rpm
Max spray output	35 kg/cm ²
Maximum discharge pressure	3.5 MPa
Maximum power speed	7000 rpm
Power output	0.7 kW
Torque, max.	1.2 Nm
Torque, max. at rpm	6000 rpm
EQUIPMENT	
Pump type	Horizontal opposed pump
LUBRICANTS	
Fuel consumption	870 g/kWh
Fuel tank volume	0.6 l
Power/fuel type	Gasoline
DIMENSIONS	
Product size height	55.6 cm
Product size length	39.5 cm
Product size width	37 cm
Weight	9.2 kg
ENGINE	
Cylinder bore	33 mm
Cylinder displacement	25.4 cm ³
Cylinder stroke	30 mm
Ignition module air gap	0.3 mm
Fuel tank volume	0.6 l
Power output	0.7 kW
Spark plug	LD L7T
PACKAGING	
Packaging height	660 mm
Packaging length	420 mm
Packaging volume	108.11 dm ³
Packaging volume	0.109 m ³
Packaging width	390 mm
Quantity in Master pack	1